

TELEHANDLERS

■ 634 ■



mustangmfg.com

tools you can COUNT ON



- Achieve a lift height of over 34 feet with a load up to 4,000 lbs.
- A strong, welded box-section boom and reinforced c-channels on the frame provide ultimate lifting performance.

- Rear axle stabilization improves stability by locking the rear axle whenever the boom is raised 60° or the parking break is applied.



- Pilot-assisted joystick controls for boom, fork tilt and frame level functions are easy-to-operate, reducing operator fatigue.



West Bend, WI USA
Tel: 262-334-9461
Fax: 262-338-7517

For more information on
Mustang equipment, call our
literature hotline at
800-628-0491
or visit our website:
mustangmfg.com

SPECIFICATIONS

		634
CAPACITIES	Lift Capacity (kg)	6000 lbs. (2722)
	Maximum Lift Height (m)	34'3" (10.4)
	Capacity at Maximum Lift Height (kg)	4000 lbs. (1814)
	Maximum Forward Reach (m)	23'3" (7.0)
	Capacity at Maximum Forward Reach (kg)	900 lbs. (408)
	Maximum Reach Below Grade (mm)	24" (610)
ENGINE	Manufacturer	John Deere
	Power (kW)	99 hp (74)
	Aspiration	Turbocharged
	Model	4045T
	Rated Speed	2500
COMPONENTS	Transmission	Dana 3-speed Powershift
	Maximum Travel Speed	20.2 mph (32.5)
	Selective Steering	4-wheel 2-wheel Crab
	Brakes	Internal Wet Disc 2-wheel Hydraulic
	Parking Brake	SAHR
HYDRAULIC SYSTEM	Axle Manufacturer	Dana
	Pump Type	Gear
	Total Capacity (L/min.)	29 gpm (110)
	System Pressure (bar)	3000 psi (207)
	Hydraulic Tank Capacity (L)	35 gal. (133)
GENERAL SPECIFICATIONS	Approximate Weight (kg)	15,100 lbs. (6850)
	Length - Less Forks (m)	16' (4.9)
	Width (m)	7'10" (2.4)
	Ground Clearance (mm)	14" (350)
	Wheelbase (m)	9'2" (2.8)
	Turning Radius (m)	12'6" (3.8)
	Overall Height (m)	7'10" (2.4)
	Frame Leveling	±10°
	Fuel Capacity (L)	29 gal. (110)
TIRE OPTIONS	15.00 x 19.5/12PR	
	15.00 x 19.5/12PR - Foam Filled	
	405/70 R20 (14.5 x R20) Radial - Traction	
	405/70 R20 (14.5 x R20) radial - Foam Filled	
	Solid-Fill	

LOAD CHART

- A** 6,000 lbs.
- B** 5,000 lbs.
- C** 4,000 lbs.
- D** 3,000 lbs.
- E** 2,000 lbs.
- F** 1,500 lbs.
- G** 1,000 lbs.
- H** 900 lbs.

